

# Installation recommendations for MACROCLEAN opaque polycarbonate sheets using MACROGLUE

#### **Necessary materials for assembly**

- Compressed air gun for cartridge of Macroglue glue.
- Macroglue quantity required: 500 gr/m<sup>2</sup> of surface.
- Double piston cartridge gun for Macroseal sealant.
- Macroseal sealant: coverage 10–12 ml per cartridge.
- Adhesive tape to protect the Macroclean sheets from the Macroseal sealant.
- Plastic roller to pass through the sheet once it has been installed so that the **Macroglue** glue is well distributed behind the sheet.
- Small spatula.
- Professional bender in case you want to bend the **Macroclean** sheet in the corners.

#### Before starting the project

Macroclean sheets are for interior surfaces.

Make sure the surfaces are smooth, free of dust and moisture. Any imperfection in the wall will be transmitted to the **Macroclean** sheet, altering its planimetry.

The glossy side of the **Macroclean** sheet is the one that matches the **Macroglue** glue, the opaque side is the side seen from the outside.


# **Macroclean sheet bonding**

It is made with the **Macroglue** cartridges and using the compressed air gun and a spatula. The **Macroclean** system with **Macroglue** has classification A+ and B-s1,d0, according to the fire regulations.

Now apply the sheet to the wall. A minimum distance of 2–3 mm must be left from the edge of the **Macroclean** sheet to both the ceiling and the floor.









### **Macroclean sheet bonding**

It is made with **Macroseal** sealant using a double piston gun. Leaving a 2-3 mm gap between the sheets and protecting the sheets with isolating tape from excess of **Macroseal** sealant (A+ and bactericide classification).



Protect the front of the sheets with adhesive tape to prevent staining.



Inject the sealant into the slot between the sheets.



After 4 or 5 minutes, spread with a spatula to remove the excess of sealant.



After ½ hour remove the tape leaving the sheet and the sealed joint uncovered.

#### **Cold bent**

**Macroclean** sheets can be cold bent with a professional bending machine without losing their mechanical or antibacterial properties.

## **Moldings**

If required, we have PVC or aluminum moldings according to the project.

**PVC moldings:** available in white color and 3 meters length.



#### **STABILIT BENELUX**